



COMMERCIAL FLOORING

- ▶ Combine colour, performance and design to deliver a durable floor finish in commercial venues and retail environments.

Commercial Flooring Technical Profile



Flowcrete's Commercial Flooring range has been developed to deliver the ultimate in aesthetic appeal, without compromising on performance.

Available in a range of attractive smooth, flaked and stone finishes, our seamless resin flooring solutions provide an appealing surface underfoot.

Durable formulations take heavy footfall and exposure to detergents and corrosive agents in their stride, ideally suited to busy public venues that might be subject to spillages and daily cleaning regimes. Added benefits of impressive slip resistance, noise reduction and versatility result in a range of flooring solutions ideally suited to a variety of commercial environments.

Application Suitability



Retail



Railways & Airports



Stadia



Education & Offices



Leisure



Healthcare

Standard Colours



Coral Tree



Deep Fir



Palm Leaf



Red Wood



Sand Dune



Wheatfield

The applied colours may differ from the examples shown. For a full colour chart and samples, contact your local Flowcrete office.



Technical Profile

TEMPERATURE RESISTANCE

RUSTIK

Tolerant of sustained temperatures up to 60°C

RUSTIK UV

Tolerant of sustained temperatures up to 65°C

SLIP RESISTANCE

TRRL Pendulum Slip Test

Dry >40
Wet 36

BOND STRENGTH

> 1.5MPa*

COMPRESSIVE STRENGTH

BS 6319

> 30N/mm²

SPEED OF CURE

Light Traffic

10°C

36 hrs

20°C

24 hrs

30°C

16 hrs

Full Traffic

72 hrs

48 hrs

36 hrs

Full Chemical Cure

12 days

7 days

6 days

*Assumes concrete compressive strength is greater than 25 N/mm²

Rustik & Rustik UV (6 mm)

Rustik and Rustik UV are colourful natural stones encapsulated in a clear resin binder.

While Rustik is ideal for use in car showrooms, offices, restaurants, retail boutiques and leisure facilities, Rustik UV's UV stable, aliphatic resin binder makes the system suitable in a range of outdoor commercial applications.



Attractive, natural stone finish



Rapid installation



Resists abrasion and chemical attack

For a full Technical Profile, contact your local Technical Department.

Technical Profile

TEMPERATURE RESISTANCE

Tolerant of sustained temperatures up to 60°C

FIRE RESISTANCE

BS 476-7 Spread of Flame	Class 2
-----------------------------	---------

SLIP RESISTANCE

TRRL Pendulum Slip Test	Dry >40
-------------------------	---------

ABRASION RESISTANCE

BS 204-2	Grade AR2
----------	-----------

COMPRESSIVE STRENGTH

BS 6319	>55 N/mm ²
---------	-----------------------

SPEED OF CURE

	10 °C	20 °C	30 °C
Light Traffic	24 hrs	20 hrs	16 hrs
Full Traffic	72 hrs	48 hrs	36 hrs
Full Chemical Cure	12 days	7 days	6 days

Mondéco Crystal (6 mm)

A highly decorative, seamless epoxy terrazzo flooring system incorporating recycled clear glass aggregates within the formulation.

Boasting impressive durability, the terrazzo system can deliver extended life cycles when compared with other flooring materials.



Contains recycled material



Aesthetically pleasing



Unique, bespoke designs



Highly durable for extended lifecycles

Standard Colours

Mondéco Crystal




Diamond



Yellow



Aquamarine



Green




Blue



Violet



Grey



Ebony

The applied colours may differ from the examples shown. For a full colour chart and samples, contact your local Flowcrete office.

Technical Profile

TEMPERATURE RESISTANCE

Tolerant of sustained temperatures up to 60°C

FIRE RESISTANCE

BS 476-7 Spread of Flame	Class 2
-----------------------------	---------

SLIP RESISTANCE

TRRL Pendulum Slip Test	Dry >40
-------------------------	---------

COMPRESSIVE STRENGTH

BS 6319	>55 N/mm ²
---------	-----------------------

FLEXURAL STRENGTH

BS 6319	>20 N/mm ²
---------	-----------------------

SPEED OF CURE	10 °C	20 °C	30 °C
Light Traffic	24 hrs	20 hrs	16 hrs
Full Traffic	72 hrs	48 hrs	36 hrs
Full Chemical Cure	12 days	7 days	6 days

Mondéco Earth (6 mm)

A highly decorative, seamless epoxy terrazzo flooring system incorporating granite and flint aggregates within the formulation.

Boasting impressive durability, the terrazzo system can deliver extended life cycles when compared with other flooring materials.



Aesthetically pleasing



Unique, bespoke designs



Highly durable for extended lifecycles

Flowfresh SRQ (4 mm)

A positively textured, quartz-based polyurethane floor system.

Containing the antimicrobial Poygiene® additive, the ultra-hygienic coating delivers extreme resistance to traffic and chemicals..



Proven antimicrobial performance



High chemical resistance



Easy to clean and sterilise



Textured anti-slip surface

Technical Profile

TEMPERATURE RESISTANCE

Tolerant of sustained temperatures up to 70°C

FIRE RESISTANCE

BS 476-7 Spread of Flame	Class 2
-----------------------------	---------

SLIP RESISTANCE

TRRL Pendulum Slip Test	Dry >60 Wet >45
-------------------------	--------------------

WATER PERMEABILITY

Karsten Test	Nil (Impermeable)
--------------	-------------------

SPEED OF CURE	10 °C	20 °C	30 °C
Light Traffic	36 hrs	24 hrs	12 hrs
Full Traffic	72 hrs	48 hrs	24 hrs
Full Chemical Cure	10 days	7 days	6 days

Technical Profile

TEMPERATURE RESISTANCE			
Tolerant of sustained temperatures up to 60°C			
FIRE RESISTANCE			
BS EN 13501-1	Class C _{fi} s1		
SLIP RESISTANCE			
TRRL Pendulum Slip Test	Dry >40		
WATER PERMEABILITY			
Karsten Test	Nil (Impermeable)		
COMPRESSIVE STRENGTH			
BS 6319	>60 N/mm ²		
SPEED OF CURE	10°C	20°C	30°C
Light Traffic	36 hrs	24 hrs	12 hrs
Full Traffic	72 hrs	48 hrs	36 hrs
Full Chemical Cure	12 days	7 days	6 days

Peran STB (3–4 mm)

A hard-wearing, decorative coating with quartz beads in a clear resin.

The positively textured floor system is ideal for use in both wet and dry environments.



Excellent abrasion and impact resistance



Decorative floor finish



High scratch resistance



Easy to clean and maintain

Flowtex TQ (4 mm)

A hard wearing, decorative epoxy floor coating system comprising colour stable quartz granules in a clear resin binder.

The seamless, positively textured finish reduces the risk of slips and trips.



Decorative, attractive finish



Excellent abrasion and impact resistance



Seamless, easy to clean finish



Resists chemicals and cleaning agents

Technical Profile

TEMPERATURE RESISTANCE			
Tolerant of sustained temperatures up to 60°C			
FIRE RESISTANCE			
BS EN 13501-1	Class C _{fi} s1		
SLIP RESISTANCE			
TRRL Pendulum Slip Test	Dry >40		
WATER PERMEABILITY			
Karsten Test	Nil (Impermeable)		
COMPRESSIVE STRENGTH			
BS 6319	>60 N/mm ²		
SPEED OF CURE	10°C	20°C	30°C
Light Traffic	36 hrs	24 hrs	12 hrs
Full Traffic	72 hrs	48 hrs	36 hrs
Full Chemical Cure	12 days	7 days	6 days


Standard Colours




Jet Black




Signal White



Pebble Grey



Light Grey



Oyster White



Light Blue

The applied colours may differ from the examples shown. For a full colour chart and samples, contact your local Flowcrete office.



Technical Profile

TEMPERATURE RESISTANCE

Tolerant of sustained temperatures up to 40°C

FIRE RESISTANCE

DIN 4102

Class 1 <50mm

SLIP RESISTANCE

BS 7976-2

Dry >40

ABRASION RESISTANCE

BS 8204-2

Class AR2

SPEED OF CURE

	10°C	20°C	30°C
Light Traffic	48 hrs	24 hrs	16 hrs
Full Traffic	96 hrs	48 hrs	48 hrs
Full Chemical Cure	14 days	5 days	4 days

Peran Comfort (2–3 mm)

Peran Comfort is a self-smoothing flexible polyurethane floor coating with an attractive, matt finish.

The colourful system is suitable for areas subject to intense traffic, including offices, retail boutiques, shopping centres, education facilities and hospitals.



Attractive and colourful floor finish



UV resistant



Self-smoothing



Hard-wearing

Technical Profile

TEMPERATURE RESISTANCE

Tolerant of sustained temperatures up to 50°C

FIRE RESISTANCE

BS 476-7
Surface Spread of Flame Class 2

SLIP RESISTANCE

BS 7976-2 Dry > 40

ABRASION RESISTANCE

BS 8204-2 Class AR2

COMPRESSIVE STRENGTH

BS 6319 55 N/mm²

SPEED OF CURE	10 °C	20 °C	30 °C
Light Traffic	24 hrs	12 hrs	6 hrs
Full Traffic	72 hrs	48 hrs	24 hrs
Full Chemical Cure	12 days	7 days	7 days

Peran SL (2–3 mm)

A colourful, glossy, self-smoothing resin floor coating system ideal for a contemporary minimalist interior design scheme.

The hard wearing finish of this attractive system resists degradation from sustained traffic and chemical attack.



Attractive, colourful finish



Seamless, easy to clean finish



Hard wearing and durable



Standard Colours



Grey 222



Beige 326



Mid Grey 280



Green 740



Sky Blue 452



Yellow 340



Tile Red 637

The applied colours may differ from the examples shown. For a full colour chart and samples, contact your local Flowcrete office.

Technical Profile

FIRE RESISTANCE	
EN 13501-1	C _{ii} -s1
SLIP RESISTANCE	
BS 7976-2 (typical values for 4-S rubber slider)	Dry > 40, Wet depends on specification (in accordance with HSE and UKSRG guidelines)
TEMPERATURE RESISTANCE	
Tolerant of sustained temperatures up to 50°C	
ABRASION RESISTANCE	
BS8204-2	Class AR2 (Medium duty industrial and commercial)
BOND STRENGTH	
> 1.5 MPa*	
SPEED OF CURE	
Walk on	1 hour
Full traffic & chemical cure	2 - 3 hours

*Assumes concrete compressive strength is greater than 25 N/mm²

Flowfast Terroso

(Thickness dependent on specification)

A seamless, decorative methyl methacrylate resin flooring system.

Installed rapidly and offering fast cure times as low as 1 hour, the floor coating system transforms environments on the fast track.



Fast curing and rapid installation



Attractive, decorative finish



Flexible application on varied substrates



Durable and resistant finish

Flowfast Kristalina

(Thickness dependent on specification)

A sparkling methyl methacrylate resin floor coating system.

Combining functionality, shimmering style and rapid installation, the quick-cure floor coating system is the ideal choice for commercial facilities.



Fast curing and rapid installation



Attractive, decorative finish



Flexible application on varied substrates



Durable and resistant finish

Technical Profile

SLIP RESISTANCE	
BS 7976-2 (typical values for 4-S rubber slider)	Dry > 40, Wet depends on specification (in accordance with HSE and UKSRG guidelines)
TEMPERATURE RESISTANCE	
Tolerant of sustained temperatures up to 50°C	
ABRASION RESISTANCE	
BS8204-2	Class AR2 (Medium duty industrial and commercial)
BOND STRENGTH	
> 1.5 MPa*	
IMPACT RESISTANCE	
EN ISO 6272	10Nm
SPEED OF CURE	
Walk on	1 hour
Full traffic & chemical cure	2 - 3 hours

*Assumes concrete compressive strength is greater than 25 N/mm²

For a full Technical Profile, contact your local Technical Department.

Technical Profile

TEMPERATURE RESISTANCE

Tolerant of sustained temperatures up to 60°C

FIRE RESISTANCE

BS 476-7
Surface Spread of Flame

Class 2

SLIP RESISTANCE

TRRL Pendulum Slip Test

Dry >40

ABRASION RESISTANCE

BS 8204-2

Class AR2

SPEED OF CURE

	10°C	20°C	30°C
Light Traffic	36 hrs	24 hrs	12 hrs
Full Traffic	72 hrs	48 hrs	24 hrs
Full Chemical Cure	12 days	7 days	6 days

Urban Expressions

(Thickness dependent on specification)

A smooth, decorative polyurethane resin floor finish available in a single tone or muted, chic multi-tonal finish.

Both finish options deliver a design statement at floor level, sure to complement modern interior design schemes.




Natural, artistic aesthetic




Seamless, easy to clean finish




Resists abrasion and chemical attack




Standard Colours Urban Expressions



Smokey Grey



Dusty Grey




Morning Coffee



Old Gold



Midnight Green



Slate Grey

The applied colours may differ from the examples shown.
For a full colour chart and samples, contact your local Flowcrete office.

Standard Colours Metallic Expressions



Blue Lagoon



Coffee



Cosmo



Grey Goose



Sangria



Merlot



Mojito



Latte

The applied colours may differ from the examples shown. For a full colour chart and samples, contact your local Flowcrete office.



Technical Profile

TEMPERATURE RESISTANCE

Tolerant of sustained temperatures up to 60°C

FIRE RESISTANCE

BS 476-7
Surface Spread of Flame

Class 1

SLIP RESISTANCE

TRRL Pendulum Slip Test

Dry >40

BOND STRENGTH

> 1.5 MPa*

SPEED OF CURE*

	10 °C	20 °C	30 °C
Light Traffic	24 hrs	12 hrs	6 hrs
Full Traffic	72 hrs	48 hrs	24 hrs
Full Chemical Cure	12 days	7 days	7 days

*Assumes concrete compressive strength is greater than 25 N/mm²

Metallic Expressions

(Thickness dependent on specification)

A highly decorative, hard wearing, advanced polyurea floor finish that provides a unique metallic finish.

The seamless finish is installed using specialist application techniques to create a molten metal effect across the surface of the floor.



Versatile design potential




Exceptional wear resistance



Seamless, easy to clean finish



UV light stable



Flowcrete

World leader in seamless resin flooring solutions and other specialist coatings.

Europe & Middle East

Baltic States	+48 883 303 880	latvia@flowcrete.com
Bulgaria	+359 898 61 58 31	bulgaria@flowcrete.com
Denmark	+46 435 40 01 10	denmark@flowcrete.com
France	+33 1 60 61 74 42	france@flowcrete.com
Germany	+49 4187 50 29 470	germany@flowcrete.com
Italy	+39 339 4853258	italy@flowcrete.com
Norway	+47 6486 0830	norway@flowcrete.com
Poland	+48 22 879 8907	poland@flowcrete.com
Romania	+40 766 596 991	romania@flowcrete.com
Russia	+7 916 931 35 13	russia@flowcrete.com
Spain	+34 937 07 0872	spain@flowcrete.com
Sweden	+46 435 40 01 10	sweden@flowcrete.com
Turkey	+90 212 294 6567	turkey@flowcrete.com
UAE	+971 4 886 4728	uae@flowcrete.com
UK	+44 1270 753 000	uk@flowcrete.com

Africa

East Africa	+254 20 682 1011	eastafrica@flowcrete.com
South Africa	+27 31 701 0017	southafrica@flowcrete.com

India

India	+91 44 4017 6600	india@flowcrete.com
-------	------------------	---------------------

Asia Pacific

Australia	+61 7 3205 7115	australia@flowcrete.com
Bangladesh	+88 02 985 7222	bangladesh@flowcrete.com
China	+86 10 8472 1912	china@flowcrete.com
Hong Kong	+852 2795 0478	hongkong@flowcrete.com
Indonesia	+62 21 252 3201	indonesia@flowcrete.com
Malaysia	+60 3 6277 9575	malaysia@flowcrete.com
Pakistan	+92 337 3159272	pakistan@flowcrete.com
Philippines	+63 2 834 6506	philippines@flowcrete.com
Singapore	+65 6848 7166	singapore@flowcrete.com
Taiwan	+886 916 954 291	taiwan@flowcrete.com
Thailand	+66 2539 3424	thailand@flowcrete.com
Vietnam	+84 28 6287 0846	vietnam@flowcrete.com

Americas

Brazil	+55 11 3230 1107	brazil@flowcrete.com
Canada	+1 604 628 1782	canada@flowcrete.com
Chile	+56 2 2938 1962	chile@flowcrete.com
Colombia	+57 1 381 9254	colombia@flowcrete.com
Mexico	+01 800 099 0468	mexico@flowcrete.com
USA	+1 936 539 6700	usa@flowcrete.com

*Whilst every care has been taken to ensure that the information included in this document was accurate at the time of printing, Flowcrete reserves the right to change product specifications at any time without prior notice. The photographs and colours reproduced in this publication are within the constraints of the printing process and are not to be used for matching purposes. All photographs are used for approximate representation only and may not show the actual products on offer. E&OE.