



TAMMSCOAT WP-IN

WATERPROOF ELASTOMERIC EXTERIOR COATING

DESCRIPTION

Tammscoat WP-IN is a unique polymer based waterproofing, elastomeric exterior performance coating to protect the concrete structure from degradation in varied climatic conditions. Tammscoat WP-IN is a single component 'Ready to Use' formulation with quick drying properties at room temperature. Its outstanding properties of water repellency coupled with toughness helps to arrest the leakage during rainy season while its stability against UV radiation keeps the brightness unfazed for years together. Its Two in One performance protects the surface from water seepage & leakage, enhances life of plaster and provides desired aesthetical outlook.

OPERATIONAL FEATURES

- Single component, ready to use system
- No water curing required.
- Quick drying at room temperature.
- Can be pigmented in wide colour range

BENEFITS

- Excellent Water Repellency
- Resistance to U.V. Radiation
- Resistance to Fungus and moss.
- Excellent Brightness and finish.
- No peel-off tendency
- Tough and Scratch-proof.
- Stable at high temperatures.

CHARACTERISTICS

Performance Data:	
Solid Content	>60% of Weight
Thickness	0.7 to 1.5 mm
Elongation	250% (ASTM D412 : 2002)
Tensile Strength	2.5 N/mm ² (ASTM D412 : 2002)
Hardness Shore A	70 N/mm ² (ASTM D2240:2002)
Crack Bridging	No Cracking Upto 1mm (10 Cycles)
Adhesion Strength	>0.6 N/mm ² (ASTM D4541:92)
UV Resistant	Excellent (ASTM G154:2000)

OTHER SALIENT FEATURES

Water Repellent

Due to its smooth film, water falling on it beads up and rolls off. Since it seals all porosity and cracks, it does not allow water to penetrate.

Water Vapour

Permeable To prevent damage from built-up hydrostatic pressure, a building must "breathe" and allow water vapour to pass through. With its multitude of densely packed micropores, Tammscoat WP-IN is much more water vapour permeable. It prevents hydrostatic pressure build up and reduces the likelihood of blistering, cracking and peeling - all while successfully repelling water!

Fungus Resistant

Due to its smooth film it does not allow fungus to grow. A powerful antifungal additive is incorporated in Tammscoat WP-IN.

UV Resistant

Tammscoat WP-IN coatings fade far less than ordinary coatings. Tammscoat WP-IN colour pigments are virtually non-reactive with ultraviolet light. Tammscoat WP-IN colours stay bright and true.

CO₂ diffusion resistant

Tammscoat WP-IN provides excellent resistance to CO₂ diffusion, which is the principle cause of damaging reinforced concrete.

Environment friendly

Tammscoat WP-IN does not release any hazardous vapours in the atmosphere and is totally environment friendly coating.

Excellent crack bridging

Tammscoat WP-IN has high degree of flexibility for wide range of temperature. The film can elongate 5 times its original shape, enabling it to conceal the cracks.

Aesthetic Decoration

Tammscoat WP-IN provides the beautiful aesthetics to the buildings combined with functional properties.

Tammscoat WP-IN can be pigmented in various shades to give a wide spectrum of colours.

Cost Effective

Tammscoat WP-IN becomes very much cost effective by avoiding reoccurring recoating cost due to its long life.

Covering Capacity

Tammscoat WP-IN covers 4-5 Sq.mt per kg. for 2 coats application depending on smoothness and porosity of substrate.

PACKAGING

Tammscoat WP-IN is packaged in 25 Kgs bucket.

SHELF LIFE

12 years. Keep container closed with a tight lid when not in use. Store in dry place.

DIRECTIONS FOR USE

Surface

Preparation Remove dust, dirt, grease, loose particles, flaking paint, wax, fungus, algae from surface using wire brush. Surface should be washed with water and allowed to dry.

Priming

Apply the priming coat using recommended primer or by mixing Tammscoat WP-IN with water in the ratio of 1:2 using brush.

Finishing

Finish by applying 2 coats of Tammscoat WP-IN with an intercoat interval of 4 hours.

Thinning

Tammscoat WP-IN is ready to apply paint, which does not require thinning.

HOW IT WORKS

Viscosity of Tammscoat WP-IN is so designed that, while application, Tammscoat WP-IN virtually travels in the surface and occupies all the cavities, porosities and hairline cracks of the structure. On curing, Tammscoat WP-IN forms tiny, flexible crystals within these cavities and blocks the passage of water arresting the chances of leakage completely. Tammscoat WP-IN, thus, on application gets absorbed in the surface and forms an integral part of it. As a result, Tammscoat WP-IN does not show any tendency of 'peel-off' in any detrimental climatic conditions.

HEALTH AND ENVIRONMENT

- The membrane does not contain any substance which is likely to be detrimental to health or to environment and complies with generally admitted 'health and safety requirements'. For more detailed information, please refer to the relevant safety data sheet.

WARRANTY: Flowcrete India Private Limited solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Flowcrete India Private Limited no other representations or statements made by Flowcrete India or its representatives, in writing or orally, shall alter this warranty. Flowcrete India MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Flowcrete India product fails to conform with this warranty, Flowcrete India will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any installation of Flowcrete India products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Flowcrete India's products for the Buyer's intended purposes.