



PLASTOL 341

MID RANGE WATER REDUCING ADMIXTURES

DESCRIPTION

PLASTOL 341 is a polycarboxylate plasticising admixture manufactured with state of the art chemistries which provides exceptional slump retention without excessive retardation in very warm temperature. Plastol 341 shows improved finishing characteristics when compared to other commonly used admixtures. Plastol 341 doesn't contain Calcium Chloride.

PRIMARY APPLICATIONS

- Ready mix concrete
- Hot weather Concreting
- Concrete mixtures utilizing Flyash, Slag or other natural pozzolans

FEATURES/BENEFITS

Plastic Concrete

- Improves finishability
- Improves workability
- Reduces water requirement
- Superior slump retention

Hardened Concrete

- Increases all strength
- Reduces permeability
- Increases durability
- Improves finished appearance

TECHNICAL INFORMATION

Performance Data:	
Appearance	Light brown liquid
Base Material	Polycarboxylate
Specific Gravity	1.08 ± 0.02 @27°C
Air entrainment	< or = 1.5% over control mix
pH	Min 6
Chloride Content	<0.2 %

Compatible with all cement types like OPC, OPC+fly ash, PPC etc.,

PACKAGING

PLASTOL 341 is packaged in bulk, and 220 Kg HDPE Barrel.

SHELF LIFE

1 Year in original, unopened container.

SPECIFICATIONS/COMPLIANCES

- Confirms the requirements of IS 9103/2007
- ASTM C 494, Type G
- AASHTO M 194

DIRECTIONS FOR USE

Normal dosage range is 200 ml - 600 ml/50 kg of cement.

However the optimum dosage is determined by site trials.

Plastol 341 should be added to initial batch water of the concrete mixture.

Do not dispense on to dry cement.

Over dosing leads to retardation of setting times of concrete, Mix may segregate and bleeding of concrete.

PRECAUTIONS/LIMITATIONS

- Care should be taken to maintain PLASTOL 341 above freezing; however, freezing and subsequent thawing will not harm the material if thoroughly agitated. Never agitate with air or an air lance.
- In all cases, refer the Safety Data Sheet before use.

WARRANTY: Flowcrete India Private Limited solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Flowcrete India Private Limited no other representations or statements made by Flowcrete India or its representatives, in writing or orally, shall alter this warranty. Flowcrete India MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Flowcrete India product fails to conform with this warranty, Flowcrete India will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any installation of Flowcrete India products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Flowcrete India's products for the Buyer's intended purposes.