



# FORMSHIELD PURE-IN

## OIL-BASED CONCRETE FORM RELEASE

### DESCRIPTION

FORMSHIELD PURE-IN is a concrete form release agent with exceptional performance and ease of use that is unmatched by oil-based form release products. FORMSHIELD PURE-IN has a unique crystal clear formulation containing a proprietary ingredient that provides release capability superior to traditional form oils. Metal, plastic, wood and composition forms strip cleanly with FORMSHIELD PURE-IN.

### PRIMARY APPLICATIONS

- Preventing the adhesion of concrete to forms of all types

### FEATURES/BENEFITS

- Forms release easily and cleanly from concrete
- No staining
- Dramatically reduces the occurrence of voids and bugholes
- Very low odour
- Tolerant to freezing conditions during storage and transportation
- Treated forms are ready for use quickly
- Easy storage and shipping.

### TECHNICAL INFORMATION

PROPERTY	RESULT
Specific Gravity	0.82-0.84 @ 27°C

### PACKAGING

FORMSHIELD PURE-IN is packaged in 200 litre drum and 20 litres container.

### SHELF LIFE

1 year in original, unopened container.

### COVERAGE

Plywood Forms/Wood	20 m <sup>2</sup> /L <sup>2</sup>
Composition Forms	
Metal Forms	40-60 m <sup>2</sup> /L <sup>2</sup>

**Note:** Coverage rates are approximate and for estimating purposes only. Surface temperature, porosity and texture will determine actual material requirements.

### DIRECTIONS FOR USE

**Surface Preparation:** The form surface must be free from dirt, cement paste, hardened concrete and other residue that could transfer to the finished concrete surface. Before coating plywood forms, apply a heavy brush coat to the plywood edges to protect laminations.

**Application:** In cold weather or if FORMSHIELD PURE-IN has been stored in a cold location, gently stir the product before using. FORMSHIELD PURE-IN can be applied by brush, spray or roller. Apply in a continuous film, avoiding excessive buildup, runs and puddles. Forms treated with FORMSHIELD PURE-IN will be ready to use within one hour on plywood and 2 to 3 hours on metal and plastic forms. Used forms can be re-coated with FORMSHIELD PURE-IN if proper surface preparation techniques are followed.

## COVERAGE

Clean tools and application equipment immediately after use with mineral spirits. Clean drips and overspray while still wet.

## PRECAUTIONS/LIMITATIONS

- Do not thin or dilute FORMSHIELD PURE-IN.
- The viscosity of FORMSHIELD PURE-IN increases at low temperatures, resulting in reduced sprayability.
- In all cases, refer the Safety Data Sheet before use.

**WARRANTY:** Flowcrete India Private Limited solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Flowcrete India Private Limited no other representations or statements made by Flowcrete India or its representatives, in writing or orally, shall alter this warranty. Flowcrete India MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Flowcrete India product fails to conform with this warranty, Flowcrete India will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any installation of Flowcrete India products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Flowcrete India's products for the Buyer's intended purposes.