

SPECIFICATIONS/COMPLIANCES

ASTM C 1315 (excluding water retention)

- ASTM C 309, Type 1, Class A & B
- USDA compliant

COVERAGE/YIELD

The coverage rate range is 7.4 – 9.8 m²/L and is highly dependent on substrate texture and porosity.

NOTE: DO NOT APPLY THICKER THAN RECOMMENDED AS THIS MAY CAUSE DISCOLORATION AND POOR PERFORMANCE.

DIRECTIONS FOR USE

Surface Preparation: The surface to be sealed with EVERCLEAR VOX must be structurally sound, clean, and dry. EVERCLEAR VOX can be applied over a previous coat of acrylic concrete sealer; however, when the chemical makeup of the previous sealer is unknown, a small test section is recommended to ensure compatibility. Premixing of EVERCLEAR VOX is not required. Do not thin or dilute with water or any other solvent. Application: Apply EVERCLEAR VOX in a uniform, continuous film by hand-held low pressure pump-up sprayer, short nap roller, or foam roller. When spraying, backroll over any sprayer overlap marks to ensure even coverage. Redistribute or remove puddles or excess EVERCLEAR VOX before it dries. Follow recommended coverage rates carefully to avoid uneven or heavy applications. For best results, two thin coats of EVERCLEAR VOX are recommended, with a minimum 1-2 hour interval between applications, following the prescribed coverage rates.

REMOVAL

Dried, cured EVERCLEAR VOX may be removed with a strong solvent such as acetone. (Always follow package directions and warning labels).

CLEAN-UP

Clean tools and equipment with water immediately following use. Clean drips and overspray with warm soapy water while still wet. If not cleaned immediately, the sealer may leave an unwanted residue on painted surfaces, glass or wood.

PRECAUTIONS/LIMITATIONS

- not allow containers of this product to freeze during transport or storage. Material becomes unusable if allowed to freeze. Store between 10°C to 38°C.
- For best application results product temperature should be between 10°C to 38°C with ambient and surface temperatures between 7°C to 35°C.
- Although compatible with many carpet, tile and floor covering adhesives, a test section is recommended to ensure good bond between the adhesive and EVERCLEAR VOX.
- In all cases, refer the Safety Data Sheet before use.

WARRANTY: Flowcrete India Private Limited solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Flowcrete India Private Limited no other representations or statements made by Flowcrete India or its representatives, in writing or orally, shall alter this warranty. Flowcrete India MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Flowcrete India product fails to conform with this warranty, Flowcrete India will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any installation of Flowcrete India products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Flowcrete India's products for the Buyer's intended purposes.